

Lutz Double Diaphragm Pumps









Model 1" Bolted Version (metallic)

Operating data / Dimensions / Weights		
	DMP 1" Aluminium	DMP 1" Stainless Steel
Housing material:	Aluminium	Stainless Steel 1.4404 (316)
Diaphragm materials:	Geolast®, Santoprene®, Teflon®, Viton®	Geolast®, Teflon®, Santoprene®, Viton®
Valve ball materials:	Geolast®, Santoprene®, Teflon®, Viton®	Geolast®, Teflon®, Santoprene®, Viton®
Seals:	Geolast®, Teflon®, Santoprene®, Viton®	Geolast®, Teflon®, Santoprene®, Viton®
Valve seat:	PP, Nylon	Stainless Steel
Flow rate:	156 l/min.	156 l/min.
Volume per stroke:	817 cm ³	817 cm ³
Suction lift dry:	4.5 m	4.5 m
Suction lift Teflon®:	3 m	3 m
Operating pressure:	max. 8.0 bar	max. 8.0 bar
Temperature limits:	93 °C	93 °C
Solids handling:	max. ø 6.4 mm	max. ø 6.4 mm
Air inlet:	1/4" NPT female (G 1/2 BSP female) ¹⁾	1/4" NPT female (G 1/2 BSP female) ¹⁾
Air outlet:	3/8" NPT female	3/8" NPT female
Suction:	1" BSP female	1" BSP female
Discharge:	1" BSP female	1" BSP female
Weight:	10.5 kg	20.4 kg

¹⁾ if the air flow control valve is used

Material description:

Geolast®	= NBR/PP-compound
Kynar®	= PVDF = Polyvinylidenfluoride
Nylon	= PA = Polyamide-compound
Polypropylene	= PP
Santoprene®	= EPDM/PP-compound
Teflon®	= PTFE = Polytetrafluorethylene
Viton®	= FPM = Fluoro Elastomer

Type	Materials of construction		Order No.
	Housing	Diaphragm, Valve balls, Seals	
DMP 1" ALB Alu/Geolast®* 	Aluminium	Geolast®	5712+000
DMP 1" ALE Alu/Santoprene®* 	Aluminium	Santoprene®	5712+040
DMP 1" ALT Alu/Teflon®* 	Aluminium	Teflon®	5712+020
DMP 1" ALV Alu/Viton®* 	Aluminium	Viton®	5712+060
DMP 1" SSB SS/Geolast®* 	Stainless Steel	Geolast®	5722+040
DMP 1" SSE SS/Santoprene®* 	Stainless Steel	Santoprene®	5722+020
DMP 1" SST SS/Teflon®* 	Stainless Steel	Teflon®	5722+000
DMP 1" SSV SS/Viton®* 	Stainless Steel	Viton®	5722+060

*Ex II 2G CT4

Teflon® and Viton® are registered Trademarks of DuPont Company. Kynar® is a registered Trademark of Pennwalt Corp. Santoprene® is a registered Trademark of Monsanto Company. Geolast® is a registered Trademark of Advanced Elastomer Systems.