

Lutz Double Diaphragm Pumps



Model 2" Clamped Version (metallic)

Operating data / Dimensions / Weights		
	DMP 2" Aluminium	DMP 2" Stainless Steel
Housing material:	Aluminium	Stainless Steel 1.4404 (316)
Diaphragm materials:	Geolast®, Teflon®, Santoprene®	Geolast®, Teflon®, Santoprene®
Valve ball materials:	Geolast®, Teflon®, Santoprene®	Geolast®, Teflon®, Santoprene®
Seals:	Geolast®, EPDM, Teflon®	Geolast®, EPDM, Teflon®
Valve seat:	PP, Nylon	Stainless Steel
Flow rate:	569 l/min.	569 l/min.
Volume per stroke:	3785 cm ³	3785 cm ³
Suction lift dry:	4.5 m	4.5 m
Suction lift Teflon®:	3 m	3 m
Operating pressure:	max. 6.8 bar	max. 6.8 bar
Temperature limits:	93 °C	93 °C
Solids handling:	max. ø 6.4 mm	max. ø 6.4 mm
Air inlet:	3/4" NPT female (3/4" BSP female) ¹⁾	3/4" NPT female (3/4" BSP female) ¹⁾
Air outlet:	3/4" NPT female	3/4" NPT female
Suction:	Flange DIN DN 50 PN 10/ ANSI B16.5 2" 150 PSI	Flange DIN DN 50 PN 10/ ANSI B16.5 2" 150 PSI
Discharge:	Flange DIN DN 50 PN 10/ ANSI B16.5 2" 150 PSI	Flange DIN DN 50 PN 10/ ANSI B16.5 2" 150 PSI
Weight:	28 kg	59 kg

¹⁾if the air flow control valve is used (not included in the delivery extent – see page 38).

Material description:

Geolast®	= NBR/PP-compound
Nylon	= PA = Polyamide-compound
Polypropylene	= PP
Santoprene®	= EPDM/PP-compound
Teflon®	= PTFE = Polytetrafluorethylene
Viton®	= FPM = Fluoro Elastomer

Type	Materials of construction		Order No.
	Housing	Diaphragm, Valve balls, Seals	
DMP 2" ALB Alu/Geolast	Aluminium	Geolast	5714-000
DMP 2" ALT Alu/Teflon®	Aluminium	Teflon®	5714-020
DMP 2" ALE Alu/Santoprene	Aluminium	Santoprene	5714-040
DMP 2" ALTS Alu/Teflon®/Santoprene®* 	Aluminium	Teflon® cond./Santoprene®	5714-021
DMP 2" SST SS/Teflon®	Stainless Steel	Teflon®	5724-000
DMP 2" SSE SS/Santoprene	Stainless Steel	Santoprene	5724-020
DMP 2" SSB SS/Geolast	Stainless Steel	Geolast	5724-040
DMP 2" SSTS SS/Teflon®/Santoprene®* 	Stainless Steel	Teflon® cond./Santoprene®	5724-021

*Ex II 2G CT4

Teflon® and Viton® are registered Trademarks of DuPont Company. Kynar® is a registered Trademark of Pennwalt Corp. Santoprene® is a registered Trademark of Monsanto Company. Geolast® is a registered Trademark of Advanced Elastomer Systems.