















## Series 600

### VITON seals

### TEFLON seals



33070	33071	33072 33073	33060	33061	33094 33096
Suitable for waste oil			Suitable for industrial use (refer to page 301)		
1:1	1:1	1:1	1:1	1:1	1:1
F1/4"G	F1/4"G	F1/4"G	F1/4"G	F1/4"G	F1/4"G
F1/2"G	F1/2"G	F1/2"G	F1/2"G	F1/2"G	F1/2"G
6-8 bar	6-8 bar	6-8 bar	6-8 bar	6-8 bar	6-8 bar
8 bar	8 bar	8 bar	8 bar	8 bar	8 bar
230 l/min	230 l/min	230 l/min	230 l/min	230 l/min	230 l/min
23 l/min	23 l/min	23 l/min	23 l/min	23 l/min	23 l/min
81 dB	81 dB	81 dB	81 dB	81 dB	81 dB
-10+50°C	-10+50°C	-10+50°C	-10+50°C	-10+50°C	-10+50°C
80 SAE	80 SAE	80 SAE	80 SAE	80 SAE	80 SAE
-	standard	standard on 33073	-	standard	standard on 33096
-	-	940 mm	-	-	940 mm
-	42 mm	42 mm	-	42 mm	42 mm
modular	customisable 1"	with drum (180-220 Kg)	modular	customisable 1"	with drum (180-220 Kg)
 No. 1 packing m <sup>3</sup> 0,006  kg 4,3	 No. 1 packing m <sup>3</sup> 0,006  kg 5	 No. 1 packing m <sup>3</sup> 0,020  kg 6,3  kg 6,4	 No. 1 packing m <sup>3</sup> 0,006  kg 4,3	 No. 1 packing m <sup>3</sup> 0,006  kg 5	 No. 1 packing m <sup>3</sup> 0,020  kg 6,3  kg 6,4