



NON-TOXIC PRESSURE SPRAYERS

Painted steel

Devices for the non-toxic spraying of low viscosity detergent liquids, such as lubrication oils and similar. Suitable for washing motor vehicles, graphiting, lubricating, delivering dismantling oils, etc. Filled to 3/4 their capacity with the required liquid and pressurised with air at 6-8 bar, they work independently without requiring continuous connection to the compressed air line.



Art. 22017 (l 16)



Art. 22024 (l 24)

Art. 22017

Portable pressure sprayer with 16-litre tank, equipped with:
 - level gauge
 - Art. 24891 antiplæh funnel

No. 1 packing m^3 0,060 kg 9,6

Art. 22024

Wheel-mounted pressure sprayer with 24-litre tank, equipped with:
 - level gauge
 - Art. 24891 antiplæh funnel

No. 1 packing m^3 0,090 kg 13

Art. 24805

Standard spray gun with EPDM seals



Art. 24801

Standard spray nozzle (equipped with filter) with delivery of approx. 1 - 1.5 l/min.



EXAMPLES OF USE

Spraying antioxidant, oil, diesel oil on mechanical parts



Spraying detergent for washing engines



Spraying detergents or protective products for machine tools



Spraying detergent for washing cars and trucks



Caution: Do not use with flammable or corrosive liquids