

# STAINLESS STEEL NON-TOXIC PRESSURE SPRAYERS

## stainless steel AISI 304

Devices for stainless steel for the non-toxic spraying of low viscosity liquids such as detergents, lubrication oils and similar.

Suitable for spraying disinfectants for agriculture, animal breeding, gardening, food, etc. Filled to 3/4 their capacity with the liquid and pressurised with air at 6-8 bar, they work independently without requiring continuous connection to the compressed air line.



Art. 23024 (j 24)





Art. 23025 (j 24)

### Art. 23024

Painted stainless steel wheel-mounted pressure sprayer with 24-litre tank, equipped with:



- level gauge
- Art. 24891 antiplash funnel

 No. 1 packing  $m^3$  0,090  kg 12,8

### Art. 23025

Stainless steel wheel-mounted pressure sprayer with 24-litre tank, equipped with:

- level gauge
- Art. 24891 antiplash funnel

 No. 1 packing  $m^3$  0,090  kg 12,8

### Art. 24806

Stainless steel standard spray gun with EPDM seals



### Art. 24891

Funnel with antiplash rim to prevent the liquid from spilling out when filling the tank.



**Important:** The stainless steel pressure sprayer can also be used with acid-base products such as sulphuric, nitric, muriatic, phosphoric acid. Make sure to choose a product that does not tend to separate and with a dilution percentage not exceeding 15 - 20%

## EXAMPLES OF USE

*Spraying of detergent or disinfectant in places containing food*



*Spraying of detergent for washing engines*



*Spraying of detergent in slaughter-houses*



*Spraying of detergent for washing public places*

